

**MRI-2351AP / RAP / TAP
SELECT SERIES INTELLIGENT SMOKE DETECTOR**



MIX-2351AP sensor mounted on a B300-6 base

Description

The Select Series low profile smoke detectors are intelligent addressable plug-in detectors with point ID capability that enables each detector address to be set with rotary address switches providing exact device locations.

Detector sensitivity is continually monitored and reported to the fire alarm control panel. These intelligent sensors utilize a state-of-the-art thermistor sensing circuit for fast response.

Advanced Protocol uses a high speed communication protocol that greatly increases the speed of communication between the intelligent devices.

The modern design and expanded color options support contemporary aesthetic demands. In addition, each detector is constructed for exceptional installation and maintenance efficiency.

The Select Series **MRI-2351AP** photoelectric detector's re-designed optical sensing chamber is engineered to sense smoke produced by a wide range of combustion sources in accordance with more stringent code standards. The sensitivity of Select Series detectors can be programmed using the control panel software to suit the environment.

The **MRI-2351RAP** photoelectric detector is also remote test capable for use with a duct smoke detector.

The **MRI-2351TAP** multi-sensor detector offers either photoelectric detection or thermal detection through dual electronic thermistors at 135°F (57°C) fixed temperature thermal sensing.

Features

- Multi-criteria detection
- Designed to meet UL 268 7th Edition and UL 521 Listed. (MIX-2351AP/TAP/RAP)
- New modern profile
- Analog communications
- Low standby current
- Rotary address switches
- Dual LEDs for 360° visibility
- Expanded color kit options

Specifications

Physical / Operating Specifications	
Height	2.0 inches (51 mm) installed in B300-6 base
Diameter	6.2 inches (156 mm) installed in B300-6 base 4.1 inches (104 mm) installed in B501-WHITE/-IV base
Shipping Weight	3.4 oz (95 g)
Operating temperature Range	Photo: 32°F to 122°F (0°C to 50°C) -4°F to 158°F (-20°C to 70°C) in duct applications Photo with Thermal: 32°F to 100°F (0°C to 38°C)
Operating Humidity Range	10% to 93% non-condensing
UL-Listed Velocity Range	Photo/Photo with Thermal: 0 to 4,000 fpm (0 to 1219 m/minute) (suitable for installation in ducts)
Electrical Specifications	
Voltage Range	15 to 32 VDC peak
Operating Current @ 24 VDC	200 uA (one communication every 5 seconds with green LED blink on communication)
Maximum Current	4.5 mA @ 24 VDC (one communication every 5 seconds with amber LED solid on)
Maximum Alarm Current	2 mA @ 24 VDC (one communication every 5 seconds with red LED solid on)



Ordering Information

Model	Description	Color
Intelligent Detectors		
MRI-2351AP	Intelligent Photoelectric smoke detector - UL	White
MRI-2351RAP	Intelligent Photoelectric smoke detector, remote test capable, for use with duct smoke detectors - UL	White
MRI-2351TAP	Intelligent Photoelectric smoke detector with Thermal - UL	White
Bases		
B501-WHITE	4" Flangeless mounting base - UL/ ULC	White
B501-IV	4" Flangeless mounting base - UL/ ULC	Ivory
B300-6	6" Flanged mounting base - UL	White
B300-6-IV	6" Flanged mounting base - UL	Ivory
B200SR-WH	Standard Sounder Base - UL	White
B200SR-IV	Standard Sounder Base - UL	Ivory
B200SR-LF-WH	Low-frequency Sounder Base - UL	White
B200SR-LF-IV	Low-frequency Sounder Base - UL	Ivory
B224BI-WH	Isolator Base - UL	White
B224BI-IV	Isolator Base - UL	Ivory
B224RB-WH	Relay Base - UL	White
B224RB-IV	Relay Base - UL	Ivory
Accessories		
CK300	Color Kit (includes cover and trim ring) - Pack of 10	White
CK300-IV	Color Kit (includes cover and trim ring) - Pack of 10	Ivory
CK300-BL	Color Kit (includes cover and trim ring) - Pack of 10	Black
TR300	Trim Ring	White
TR300-IR	Trim Ring	Ivory
RA100Z	Remote LED annunciator - UL	Ivory

THIS INFORMATION IS FOR MARKETING PURPOSES ONLY AND NOT INTENDED TO DESCRIBE THE PRODUCTS TECHNICALLY.

For complete and accurate technical information relating to performance, installation, testing and certification, refer to technical literature. This document contains intellectual property of Mircom. The information is subject to change by Mircom without notice. Mircom does not represent or warrant correctness or completeness.

SECUTRON Catalog Number

4036

Issue 1
Page 2 of 2