



400 Series LED Horns, Strobes and Horn/Strobes



Compact Energy Efficient Audible/Visual Solution

MGC's 400 Series LED Notification Appliances offer an audible/visual solution that delivers exceptional energy efficiency in a compact design.

Utilizing advanced LED technology, the MGC's 400 Series LED Notification Appliances provide a lower current draw which allows for more devices on a NAC circuit while reducing the number of external power supplies required.

Designed for indoor/outdoor, wall or ceiling mount applications, MGC's 400 Series offer multiple field-selectable audible/visual settings, red and white options for flexibility as well as a wide range of mounting options in an easy to install compact unit.

MGC's Notification Appliances comply with agency requirements including the NFPA 72, UL 464, UL 1971, UL1638, UL1480, ULC S525, ULC S526 and ULC S541.

- Energy Efficient
- Flexible
- Safe
- Easy to install



Wall/Ceiling Mount
Horns



Wall Mount
Strobes



Wall Mount
Horn/Strobes



Low Frequency
Wall/Ceiling Mount
Sounder



Low Frequency
Wall Mount
Sounder Strobe



Ceiling Mount
Strobes



Ceiling Mount
Horns/Strobes



Weather Protected
Wall/Ceiling Mount Horn



Weather Protected
Wall Mount Strobe



Weather Protected
Wall Mount Horn/Strobe

FEATURES

- Standard and high candela settings in one unit (Horn Strobe) to meet virtually any application
 - Wall Mount models:
15, 15/75, 30, 75, 110, 185 cd
 - Ceiling Mount models:
15, 15/75, 30, 75, 110 cd
 - Reduction in SKUs to stock
- Multiple field-selectable audible settings
 - Temporal, Continuous, March Time and 20 BPM audible tones
 - High and low volume settings
- Weather Protected Devices
Temperature ranges from -40°C to 66°C (-40°F to 151°F)
- Low Frequency 520 Hz operation range

ENERGY EFFICIENT

- Advanced LED technology provides superior current draw performance
 - Allows for a higher capacity of notification devices per circuit
 - Eases external power supply requirements

SAFE

- Device settings are located on the back of the unit to prevent tampering
- Compliance
 - UL 1971, UL 1638, UL 464
 - ULC-S525, ULC-S526
 - NFPA 72

EASY TO INSTALL

- Indoor & Standard frequency models include a mounting plate that allows for devices to be pre-wired.
- Wide range of mounting options
 - Mount to Mircom BB-400 surface mount back box, single gang, 4-inch square, double gang, octagon and 4-inch junction boxes

Wall/Ceiling Mount Horns	
FH-400-RR	Red
FH-400-WW	White
FH-400-RR-WP	Weather Protected, Red
FH-400-RR-LF	Low Frequency, Red
FH-400-WW-LF	Low Frequency, White
Wall Mount Strobes	
FS-400-RR	Red
FS-400-WW	White
FS-400-RR-WP	Weather Protected - Red
Wall Mount Horn/Strobes	
FHS-400-RR	Red
FHS-400-WW	White
FHS-400-RR-WP	Weather Protected - Red
FHS-400-RR-LF	Low Frequency, Red
FHS-400-WW-LF	Low Frequency, White
Ceiling Mount Strobes	
FS-400C-RR	Red
FS-400C-WW	White
Ceiling Mount Horns/Strobes	
FHS-400C-RR	Red
FHS-400C-WW	White
Accessories	
MIX-4050	MGC SYNC module
MRI-4050	Secutron SYNC module