

SPP/SPPS SERIES SPEAKERS & LED SPEAKER/STROBES

Compact energy efficient audible/visual solution

MGC's Speakers and Speaker/Strobes extend the notification appliance offering to provide a complete family lineup which utilizes advanced LED technology.

Designed for indoor/outdoor wall or ceiling mount applications, MGC's Speakers and Speaker/Strobes are offered in 25/70V, 1/4, 1/2, 1 or 2 W, high candela and red/white options for flexibility.

MGC also offers a trim plate/adapter kit for applications where ceiling back box space is limited. External sync module for compatibility with any UL FACU or PSU.

MGC's Speaker and Speaker/Strobes comply with agency requirements including the NFPA 72, UL 1971, UL 1638, UL 1480, ULC S526 and ULC S541.

- Energy Efficient
- Flexible
- Safe
- Easy to install





Ceiling Mount Speakers



Ceiling Mount Speakers/Strobes



Ceiling Mount Accessories



Wall Mount Speakers



Wall Mount Speaker/Strobes



Weather Protected
Wall/Ceiling Mount Speaker



Weather Protected
Wall Mount Speaker/Strobe

FEATURES

- All models with 25V/70V options
- All models with RED or WHITE options
- Speaker Power Setting: ¼, ½, 1, 2 W
- Built-in Synchronization Candela Settings for Speaker/Strobes
- Wall Mount models: 15, 30, 75, 110, 185, 15/75 cd
- Ceiling Mount models: 15, 30, 75, 110, 125, 15/75 cd
- Ceiling Mount High Candela models: 50, 75, 90, 130, 185, 15/75 cd
- Weather Protected Devices Temperature ranges from -40°C to 66°C (-40°F to 151°F)

ENERGY EFFICIENT

- Advanced LED technology provides ultra low current draw performance
 - o Allows for a higher capacity of notification devices per circuit
 - o Eases external power supply requirements

FLEXIBLE

- Multiple language plastic inserts included with speaker/strobes (English/French/Spanish)

SAFE

- Device settings are located on the back of the unit to prevent tampering
- Compliance
 - o UL 1480, UL 1971 and UL 1638
 - o ULC-S541 and ULC-S526
 - o NFPA 72 (Meets 20 millisecond pulse width requirement)

EASY TO INSTALL

- Wall models can be mounted directly onto a 4" square back box.
- Ceiling model can be mounted on a 6" round flush back box (IB-104)
- Optional spacer (SPKC-W) for mounting on a 4" square electrical box

Ceiling Mount Speakers

SPP-104-25	White
SPP-104-70	White
SPP-104-25R	Red
SPP-104-70R	Red

Ceiling Mount Speakers/Strobes

SPPS-104-25	White
SPPS-104-70	White
SPPS-104-25R	Red
SPPS-104-70R	Red
SPPS-104-25H	High candela White
SPPS-104-70H	High candela White
SPPS-104-25HR	High candela Red
SPPS-104-70HR	High candela Red

Wall Mount Speakers

SPP-204-25	White
SPP-204-70	White
SPP-204-25R	Red
SPP-204-70R	Red

Wall Mount Speaker/Strobes

SPPS-204-25	White
SPPS-204-70	White
SPPS-204-25R	Red
SPPS-204-70R	Red
SPPS-204-25R-WP	Weather Protected - Red
SPPS-204-70R-WP	Weather Protected - Red

Weather Protected Wall/Ceiling Mount Speakers

SPP-204-25R-WP	Red
SPP-204-70R-WP	Red

Accessories

IB-104	6" Back Box
SPKC-W	Spacer/trim ring
MIX-4050	MGC SYNC module
MRI-4050	Secutron SYNC module